




Lamp height




Extension of swing arm



Shade dimensions



Exit through side



Extended pipe

## MODIFICATIONS AND SPECIAL CONTRACTS

Nessen will endeavor to fulfill all reasonable and implementable requests for modifications to standard lamps and for contract quantities.

For instance, we can modify the height of a lamp, make a swing-arm longer or shorter, relocate a switch, offer custom enamel paints, use fluorescent instead of incandescent technology, alter shade dimensions and fabrics and use special wiring.

Such accommodations are made for two reasons: to meet specific design requirements or to up- or down-scale features to meet quality and budget considerations on larger orders.

No minimum quantities are required for special orders. Pricing will be determined by the nature of the changes and the quantities involved.

## FINISHES

**Standard:** As specified on catalog page

- Optional:**
- Polished Brass
  - Polished Chrome
  - Brushed Brass
  - Satin Chrome
  - Baked enamel paint — for accurate quotations, paint chips and/or Pantone numbers are required. Please specify gloss, matte or crinkle finish.

## FIXTURE DIMENSIONS

**Standard:** As specified on catalog page

- Optional:**
- Lamp height — specify new dimension
  - Extension of swing arm — specify new dimension
  - Fixed height upright tube — specify desired height
  - Telescopic upright tube on floor lamps (telescoping lamps cannot be painted)

## SHADE FABRICS/DIMENSIONS


**Standard:** As specified on catalog page

- Optional:**
- Fire retardant white linen
  - Nesclean vinyl material (washable)
  - To change dimensions, refer to pages 3, 4 and 5 in the Pricing Guide for available options . . . also specify amount of "break" desired, if any.
  - Glass diffuser shade support
  - Harp style shade support

## EXTENDED PIPE (EP)

**Standard:** As specified on catalog page

- Optional:**
- A- Most table lamps can be fitted with an extended pipe for through-surface installation . . . this variation conserves work surface space, provides greater stability, minimizes potential for theft and insures integrity of the original design.
  - B- Standard extended pipe fittings take 1 1/8" diam. hole, cord exits through bottom (for tables not exceeding 1" thickness)
  - C- For fixtures using 3-conductor or hospital grade cord, a 1 3/8" diam. hole is required.
  - D- Specify cord exit through side if cord cannot exit from furniture (eg., end table with drawers)
  - E- Specify diameter of larger cover plate if needed for existing grommet holes
  - F- Specify if longer extension needed for tables thicker than 1"
  - G- Specify choice of finishing disc or regular base




S-cluster

### SWITCH LOCATION

**Standard:** As specified on catalog page

- Optional:**
- Move to cup
  - Move to socket
  - Move to tube
  - Move to base
  - Move to in-line
  - Eliminate for touch dimmer (where design permits)




Drop cluster

### SWITCH TYPES

**Standard:** As specified on catalog page

- Optional:**
- On/Off switch
  - Three-way switch
  - Dimmer in socket
  - Pull chain
  - In-line On/Off
  - In-line Dimmer
  - Touch dimmer




Quick-disconnect

### SOCKETS

**Standard:** Bakelite, unless otherwise noted

- Optional:**
- Porcelain (to minimize hazards from over-lamping)
  - Pull chain
  - S-cluster
  - Drop cluster
  - Single socket
  - Halogen socket



Standard grade 3-conductor

### CORD COLOR

**Standard:** 6 feet of 2-conductor cord. Fixtures with plug-in ballasts come with “quick-disconnect” cords which separate in-line to allow threading through office system grommets and permit connections at table or desk-top level as well as at wall or floor mounted sockets.


- Standard Colors:**
- Polished Brass — gold cord
  - Polished Chrome — grey cord
  - Plug-in ballast — black cord

- Optional:**
- 2-conductor cord — brown, white
  - 3-conductor cord — white, black, grey
  - Hospital grade 3-conductor cord — grey only

### BULBS

**Standard:** As specified on catalog page

- Optional:**
- Fluorescent (non-dimmable)
  - Incandescent (easily dimmable, warm color)
  - Halogen (easily dimmable, truest color rendition)



L-shape 3-conductor plug

### PLUGS

**Standard:** As specified on catalog page

- Optional:**
- 3-conductor plug
  - Hospital grade 3-conductor plug (green dot)
  - L-shape 3-conductor plug (as commonly used with refrigerators, permits restricted space connections without undue bending stress on the wire)